

WX Tumble Dryers

FEATURES

- Easy to use timer
- Electrical, Gas and Steam heating
- Large door opening for easy
- Galvanized drum
- Axial airflow
- Large lint filter

OPTIONS

- Stainless steel drum
- Coin operated version
- Reversing drum
- Residual moisture control



TYPE		WX25	WX30	WX35	WX55
CAPACITY					
Capacity	kg	11,5	13,5	16	24
Drum volume	l	217	271	347	491
Drum diameter	mm	Ø673	Ø673	Ø762	Ø838
AIRFLOW					
50 Hz	l/s	203	203	260	283
60 Hz	l/s	236	236	307	330
DRYING AVERAGE					
Gas heating	g/min	222	258	331	444
Electric heating	g/min	172	272	335	399
MOTOR					
Fan	kW	0,187	0,187	0,187	0,375
Drive	kW	0,187	0,187	0,187	0,375
GAS HEATING					
Energy	kW	18,8	21,4	26,4	29,9
Energy	kBTU/h	64	73	90	102
Electrical connection		1×200-240V 50/60Hz, 3×200-240V 50/60Hz 3×380-415V 50Hz, 3×380-415/440V 60Hz			
Gas connection	NPT	½"	½"	½"	½"
STEAM HEATING					
High pressure 6,9 bar	kW	39,6	39,5	48,6	-
	kBTU/h	135	134,7	166	-
Electrical connection		1×200-240V 50/60Hz, 3×200-240V 50/60Hz 3×380-415V 50Hz, 3×380-415/440V 60Hz			
Steam connection	NPT	¾"	¾"	¾"	-
ELECTRICAL HEATING					
Energy	kW	12	21	24	27
Electrical connection		3×200-240V 50/60Hz, 3×380-415 50Hz, 3×380-415/440V 60Hz			
EXHAUST	Ø/mm	152	152	203	203
DIMENSIONS					
H×W×D	mm	1622×711×1038	1622×711×1191	1622×800×1191	1695×876×1362
Net weight	kg	137	150	164	197
TRANSPORT DATA					
Gross weight	kg	151	165	179	216
Packing H×W×D	mm	1753×762×1092	1753×762×1245	1753×838×1245	1829×902×1489

All specification and images subject to change without notice. Manufactured specially for Warwick by Alliance Laundry Systems

